

TRIOSUN™

A TRIOSILO PRODUCT

PRODUCT DATA TRIOSUN 110µ Black/Black

Items	Dimensions [m x µ x m]	Reels/pallet [pce]	Core	Pallet dimension [mm x mm]
28836	10 x 110 x 50	11	Cardboard	1100 x 1500
28837	12 x 110 x 50	11	Cardboard	1100 x 1700
28838	14 x 110 x 50	11	Cardboard	1100 x 1900
28839	16 x 110 x 50	11	Cardboard	1100 x 2250
28840	18 x 110 x 50	11	Cardboard	1100 x 2500
28866	10 x 110 x 400	1	PVC	800 x 1500
28867	12 x 110 x 400	1	PVC	800 x 1800
28868	14 x 110 x 400	1	PVC	800 x 2100
28869	16 x 110 x 400	1	PVC	800 x 2400
28870	18 x 110 x 400	1	PVC	800 x 2600

TECHNICAL DATA

Dart Drop	Tensile Strength	Tear resistance	Elongation at Break	UV	OTR
>600 g	MD: 28 Mpa	MD: >9000 mN	MD: 600 %	24 months	<250 cm ³ /24h
	TD : 28 Mpa	TD : >25 000 mN	TD : 700 %		

ENVIRONMENTAL PERFORMANCE

	Recycling material	PCR rate	recyclable	reduce CO ²
value	72%	69%	100%	-54%
Certification	EuCertPlast	RecyClass		SimaPro

*LCA (Life Cycle Assessment): Comparison of the carbon footprint of 100% virgin film and TrioSILO film, made from recycled material. Standardised comparative method SimaPro.

Above data is only intended for information and could be changed without previous notice. Other sizes can be manufactured to order with minimum volume. Every endeavor has been made to ensure that the information given herein is true and reliable but is given only for guidance of our customers.

TRIOSUN™

A TRIOSILO PRODUCT

PRODUCT DATA TRIOSUN 115 μ Black/White

Items	Dimensions [m x μ x m]	Reels/pallet [pce]	Core	Pallet dimension [mm x mm]
29008	8 x 115 x 50	11	Cardboard	1100 x 1300
28830	10 x 115 x 50	11	Cardboard	1100 x 1500
28831	12 x 115 x 50	11	Cardboard	1100 x 1700
28832	14 x 115 x 50	11	Cardboard	1100 x 1900
28833	16 x 115 x 50	11	Cardboard	1100 x 2250
28834	18 x 115 x 50	11	Cardboard	1100 x 2500
29029	6 x 115 x 300	1	PVC	800 x 1300
29014	8 x 115 x 300	1	PVC	800 x 1300
29009	10 x 115 x 300	1	PVC	800 x 1500
29010	12 x 115 x 300	1	PVC	800 x 1800
29011	14 x 115 x 300	1	PVC	800 x 2100
29012	16 x 115 x 300	1	PVC	800 x 2400
29013	18 x 115 x 300	1	PVC	800 x 2600
29052	9 x 115 x 400	1	PVC	800 x 1500
28871	10 x 115 x 400	1	PVC	800 x 1500
29051	12 x 115 x 400	1	PVC	800 x 1800
28872	14 x 115 x 400	1	PVC	800 x 2100
28873	16 x 115 x 400	1	PVC	800 x 2400
28875	18 x 115 x 400	1	PVC	800 x 2600

TECHNICAL DATA

Dart Drop	Tensile Strength	Tear resistance	Elongation at Break	UV	OTR
>600 g	MD: 28 Mpa	MD: >9000 mN	MD: 600 %	24months	<250 cm ³ /24h
	TD: 28 Mpa	TD: >25 000 mN	TD: 700 %		

ENVIRONMENTAL PERFROMANCE

	Recycling material	PCR rate	recyclable	reduce CO ²
value	54%	51%	100%	-54%
Certification	EuCertPlast	RecyClass		SimaPro

*LCA (Life Cycle Assessment): Comparison of the carbon footprint of 100% virgin film and TrioSILO film, made from recycled material. Standardised comparative method SimaPro.

Above data is only intended for information and could be changed without previous notice. Other sizes can be manufactured to order with minimum volume. Every endeavor has been made to ensure that the information given herein is true and reliable but is given only for guidance of our customers.

TRIOSUN™

A TRIOSILO PRODUCT

PRODUCT DATA TRIOSUN 115µ Black/Green

Items	Dimensions [m x µ x m]	Reels/pallet [pce]	Core	Pallet dimension [mm x mm]
28825	10 x 115 x 50	11	Cardboard	1100 x 1500
28826	12 x 115 x 50	11	Cardboard	1100 x 1700
28827	14 x 115 x 50	11	Cardboard	1100 x 2000
28828	16 x 115 x 50	11	Cardboard	1100 x 2250
28829	18 x 115 x 50	11	Cardboard	1100 x 2500
28091	8 x 115 x 408M ²	23	Cardboard	1200 x 1400
28087	10 x 115 x 408M ²	23	Cardboard	1100 x 1500
28088	12 x 115 x 408M ²	23	Cardboard	1100 x 1700
28089	14 x 115 x 490M ²	23	Cardboard	1100 x 2000
28090	16 x 115 x 560M ²	14	Cardboard	1100 x 2250
29065	6 x 115 x 300	1	PVC	800 x 1700
29066	8 x 115 x 300	1	PVC	800 x 1400
29067	10 x 115 x 300	1	PVC	800 x 1500
29068	12 x 115 x 300	1	PVC	800 x 1700
28580	14 x 115 x 300	1	PVC	800 x 2100
28581	16 x 115 x 300	1	PVC	800 x 2300
28904	18 x 115 x 300	1	PVC	800 x 2500
29053	9 x 115 x 400	1	PVC	800 x 1400
29054	10 x 115 x 400	1	PVC	800 x 1500
29055	11 x 115 x 400	1	PVC	800 x 1700
29056	12 x 115 x 400	1	PVC	800 x 1700
29057	14 x 115 x 400	1	PVC	800 x 2100

TECHNICAL DATA

Dart Drop	Tensile Strength	Tear resistance	Elongation at Break	UV	OTR
>600 g	MD: 28 Mpa TD : 28 Mpa	MD: >9000 mN TD : >25 000 mN	MD: 600 % TD : 700 %	24 mon-ths	<250 cm ³ /24h

ENVIRONMENTAL PERFORMANCE

	Recycling material	PCR rate	recyclable	reduce CO ²
value	71%	68%	100%	-54%
Certification	EuCertPlast	RecyClass		SimaPro

*LCA (Life Cycle Assessment): Comparison of the carbon footprint of 100% virgin film and TrioSILO film, made from recycled material. Standardised comparative method SimaPro.

Above data is only intended for information and could be changed without previous notice. Other sizes can be manufactured to order with minimum volume. Every endeavor has been made to ensure that the information given herein is true and reliable but is given only for guidance of our customers.

TRIOSUN™

A TRIOSILO PRODUCT

PRODUCT DATA TRIOSUN 115 μ White/White

Items	Dimensions [m x μ x m]	Reels/pallet [pce]	Core	Pallet dimension [mm x mm]
28986	6 x 115 x 30	35	Cardboard	1100 x 1700
28987	8 x 115 x 30	25	Cardboard	1100 x 1300
28988	10 x 115 x 30	25	Cardboard	1100 x 1500
28989	12 x 115 x 30	20	Cardboard	1100 x 1700
28990	14 x 115 x 30	20	Cardboard	1100 x 2000
28991	16 x 115 x 30	20	Cardboard	1100 x 2300
28992	18 x 115 x 30	15	Cardboard	1100 x 2500
28733	6 x 115 x 50	28	Cardboard	1200 x 1700
28734	8 x 115 x 50	18	Cardboard	1200 x 1200
28735	10 x 115 x 50	18	Cardboard	1200 x 1500
28736	12 x 115 x 50	18	Cardboard	1200 x 1700
28737	14 x 115 x 50	14	Cardboard	1200 x 2000
28738	16 x 115 x 50	14	Cardboard	1200 x 2300
28739	18 x 115 x 50	11	Cardboard	1200 x 2500
21048	6 x 115 x 300	2	PVC	1200 x 1800
21049	8 x 115 x 300	2	PVC	1200 x 1300
21050	10 x 115 x 300	2	PVC	1200 x 1500
21051	12 x 115 x 300	2	PVC	1200 x 1900
21052	14 x 115 x 300	2	PVC	1200 x 2100
21082	16 x 115 x 300	1	PVC	800 x 2300
28064	18 x 115 x 300	1	PVC	800 x 2600

TECHNICAL DATA

Dart Drop	Tensile Strength	Tear resistance	Elongation at Break	UV	OTR
>600 g	MD: 28 Mpa TD : 28 Mpa	MD: >9000 mN TD : >25 000 mN	MD: 600 % TD : 700 %	24 mon- ths	<250 cm ³ /24h

ENVIRONMENTAL PERFORMANCE

	Recycling material	PCR rate	recyclable	reduce CO ²
value	>64%	64%	100%	-54%
Certification	EuCertPlast	RecyClass		SimaPro

*LCA (Life Cycle Assessment): Comparison of the carbon footprint of 100% virgin film and TrioSILO film, made from recycled material. Standardised comparative method SimaPro.

Above data is only intended for information and could be changed without previous notice. Other sizes can be manufactured to order with minimum volume. Every endeavor has been made to ensure that the information given herein is true and reliable but is given only for guidance of our customers.